



SolarEdge Commercial Three Phase Inverters

SE50K / SE55K / SE82.8K



INVERTERS

Specifically designed to work with power optimizers

- Easy two-person installation – each unit mounted separately, equipped with cables for simple connection between units
- Balance of System and labor reduction compared to using multiple smaller string inverters
- Independent operation of each unit enables higher uptime and easy serviceability
- No wasted ground area: wall/rail mounted or horizontally mounted under the modules (10° inclination)
- Built-in module-level monitoring with Ethernet or cellular GSM
- Fixed voltage inverter for superior efficiency (98.3%) and longer strings
- Integrated DC Safety Unit with DC Safety Switch and optional surge protection & DC fuses – eliminates the need for external DC isolators
- Built-in RS485 Surge Protection Device, to better withstand lightning events



SolarEdge Commercial Three Phase Inverters SE50K / SE55K / SE82.8K

	SE50K ⁽¹⁾	SE55K	SE82.8K	
OUTPUT				
Rated AC Power Output	50000 ⁽²⁾	55000	82800	VA
Maximum AC Power Output	50000 ⁽²⁾	55000	82800	VA
AC Output Voltage — Line to Line / Line to Neutral (Nominal)	380/220 ; 400/230			Vac
AC Output Voltage — Line to Line Range; Line to Neutral Range	318 - 460; 184 - 264.5			Vac
AC Frequency	50/60 ± 5			Hz
Maximum Continuous Output Current (per Phase) @Vac,nom	76	80	120	A
Grids Supported — Three Phase	3 / N / PE (WYE with Neutral)			V
Maximum Residual Current Injection Utility Monitoring, Islanding Protection, Configurable Power Factor, Country Configurable Thresholds	250 per unit ⁽³⁾			mA
	Yes			
INPUT				
Maximum DC Power (Module STC), Inverter / Unit	67500 / 33750	74500 / 37250	111750 / 37250	W
Transformer-less, Ungrounded	Yes			
Maximum Input Voltage	1000			Vdc
Nominal DC Input Voltage	750			Vdc
Maximum Input Current	74	80	120	Adc
Reverse-Polarity Protection	Yes			
Ground-Fault Isolation Detection	350kΩ Sensitivity per Unit ⁽⁴⁾			
Maximum Inverter Efficiency	98.3			%
European Weighted Efficiency	98			%
Nighttime Power Consumption	< 12			W
ADDITIONAL FEATURES				
Supported Communication Interfaces ⁽⁵⁾	RS485, Ethernet, Cellular GSM (optional)			
RS485 Surge Protection	Built-in			
DC SAFETY UNIT				
DC Disconnect	1000V / 2 x 40A		1000V / 3 x 40A	
DC Surge Protection	Optional, type II, field replaceable			
DC Fuses on Plus & Minus	Optional, 30A			
STANDARD COMPLIANCE⁽⁶⁾				
Safety	IEC-62109, AS3100			
Grid Connection Standards ⁽⁷⁾	VDE-AR-N-4105, G59/3, AS-4777, EN 50438, CEI-021, VDE 0126-1-1, CEI-016, BDEW			
Emissions	IEC61000-6-2, IEC61000-6-3, IEC61000-3-11, IEC61000-3-12			
RoHS	Yes			
INSTALLATION SPECIFICATIONS				
Number of Units	2		3	
AC Output Cable	Cable gland — diameter 22-32; PE gland diameter 10-16		Cable gland — diameter 20-38; PE gland diameter 10-16	mm
DC Input ⁽⁸⁾	6 strings, 4-10mm ² DC wire, gland outer diameter 5-10mm		9 strings, 4-10mm ² DC wire, gland outer diameter 5-10mm	
AC Output Wire	Aluminum or Copper; L, N: Up to 70, PE: Up to 35		Aluminum or Copper; L, N: Up to 95, PE: Up to 50	mm ²
Dimensions (H x W x D)	Primary Unit: 940 x 315 x 260; Secondary Unit: 540 x 315 x 260			mm
Weight	Primary Unit: 48; Secondary Unit: 45			kg
Operating Temperature Range	-40 to +60 ⁽⁹⁾			°C
Cooling	Fan (user replaceable)			
Noise	< 60			dBA
Protection Rating	IP65 — Outdoor and Indoor			
Bracket Mounted (Brackets Provided)				

⁽¹⁾ Available in the UK and in Israel

⁽²⁾ 49990 in the UK

⁽³⁾ If an external RCD is required, its trip value must be ≥ 300mA per unit (≥ 600mA for SE50K/SE55K; ≥ 900mA for SE82.8K)

⁽⁴⁾ Where permitted by local regulations

⁽⁵⁾ Refer to Datasheets -> Communications category on Downloads page for specifications of optional communication options: <http://www.solaredge.com/groups/support/downloads>

⁽⁶⁾ Pending

⁽⁷⁾ For all standards refer to Certifications category on Downloads page: <http://www.solaredge.com/groups/support/downloads>

⁽⁸⁾ Single input option per unit (up to 25mm²) available

⁽⁹⁾ For power de-rating information refer to: <https://www.solaredge.com/sites/default/files/se-temperature-derating-note.pdf>

